

2024 Catalog

INDEX




- 3 Bakerlux Convection Ovens
- 6 Bakerlux Ventless Hoods
- 8 Bakerlux Stations
- 10 VariKwik Speed Ovens
- 12 VariKwik Accessories
- 14 XAF Convection Ovens
- 16 **OV Convection Ovens**
- 21 Panini Grills
- 23 Toasters
- 24 Griddles
- 25 Hot Plates
- 27 Electric Chafers / Buffet Servers
- 39 Warming Shelves
- 33 Pass & Go Warmers
- 37 Warranty & Service Info
- 38 Ordering & Shipping
- 39 Sales Reps





"Our BakerLux pumps out products at an accelerated rate and the end results are incredibly consistent. The overall quality of the BakerLux oven, coupled with its performance, makes for another reason why Cadco equipment is an essential staple in all foodservice operations."

— Joe Muench, Chef/Owner,





Black Shoe Hospitality







BAKERLUX™ Ovens

HEAVY DUTY DIGITAL

NSF MET (UL & CSA)





- Shelves included 3 baking steps
- Up to 99 programs, including 12 "Quick Access" programs
- Handles standard half size sheet pans (not included) I fan speed
- · Light flashes and unit beeps at end of cooking cycle
- No water pump; cannot run proofer
- *Ship weights include shipping skid (approx. 40 lbs.)

GO MODEL (No Humidity)

- Advanced airflow design & automatically reversible fan for even baking
- Heat settings from 175° -500° F
- 10 hour timer or continuous on
- Heavy duty stainless steel construction
- Extra large motor for long lasting use
- 2-5/8" between shelves
- Interior LED light
- "Cool-touch" double wall glass door
- Heavy duty door and hinge construction
- Auto shut off when door is opened
- Energy Star rated
- Requires dedicated electrical line
- Stackable with optional Stacking Kit
- 2 Year Limited On-site Warranty
- Freight class 200. **NOTE:** These models must ship by truck, not UPS

Model	Description Cavity size: W" x H" x D"	Size/ Shelves	Volts	Watts	Amps	Unit Dimensions W" x H" x D"	Ship Wt. (lbs.)	
XAFT-03HS-GD	19 1/4 x 10 1/4 x 14; 1.6 cft. One fan. NEMA 5-15P plug.	Half 3	120	1440	12	23 5/8 x 16 5/8 x 29	130*	



LED MODEL (With Humidity)

- Shelves included 3 baking steps
- Includes electro valve for direct plumbed water connection
- Up to 99 programs, including 12 "Quick Access" programs
- Handles standard half size or full size sheet pans (not included)
 2 fan speeds
- Light flashes and unit beeps at end of cooking cycle
- Can run optional proofer
- *Ship weights include shipping skid (approx. 40 lbs.)





NEMA 6-50 P Plug

Model	Description Cavity size: W" x H" x D"	Size/ Shelves	Volts	Watts	Amps	Unit Dimensions W" x H" x D"	Ship Wt. (lbs.)
XAFT-03HS-LD	19 1/4 x 10 1/4 x 14; 1.6 cft. One fan. NEMA 6-20P plug.	Half 3	208-240	3300	14	23 5/8 × 16 5/8 × 29	130*
XAFT-04HS-LD	19 1/4 x 13 1/4 x 14; 2.1 cft. One fan. NEMA 6-20P plug.	Half 4	208-240	3800	16	23 5/8 x 19 5/8 x 29	139*
XAFT-04FS-LD	27 1/4 x 13 1/4 x 19; 4 cft. Two fans. NEMA 6-50P plug.	Full 4	208-240	7600	32	31 1/2 x 19 5/8 x 35 1/2	190*

BAKERLUX™ Ovens

HEAVY DUTY DIGITAL

NSF MET (UL & CSA)

TOUCH MODEL

BAKELUX SHQPPrograms TOUCH BAKELUX SHQPPrograms Cadco SHQPPrograms Cadco

XAFT-04FS-TD shown

(With Top-Opening Door & Humidity)

- Shelves included 9 baking steps
- Up to 99 programs with graphic control panel
- Includes electro valve for direct plumbed water connection
- Handles standard half size or full size sheet pans (not included)
- 2 fan speeds
- Light flashes and unit beeps at end of cooking cycle
- USB programming capability
- Data driven cooking Can run optional proofer
- Freight class 200. **NOTE:** These models must ship by truck, not UPS
- *Ship weights include shipping skid (approx. 40 lbs.)



NEMA 6-20 P Plug



NEMA 6-50 P Plug

Model	Description Cavity size: W" x H" x D"	Size/ Shelves	Volts	Watts	Amps	Unit Dimensions W" x H" x D"	Ship Wt. (lbs.)
XAFT-03HS-TD	19 1/4 x 10 1/4 x 14; 1.6 cft. One fan. NEMA 6-20P plug.	Half 3	208-240	3300	14	23 5/8 x 16 5/8 x 29	130*
XAFT-04HS-TD	19 1/4 x 13 1/4 x 14; 2.1 cft. One fan. NEMA 6-20P plug.	Half 4	208-240	3800	16	23 5/8 x 19 5/8 x 29	139*
XAFT-04FS-TD	27 1/4 x 13 1/4 x 19; 4 cft. Two fans. NEMA 6-50P plug.	Full 4	208-240	7600	32	31 1/2 x 19 5/8 x 351/2	190*







NEMA 6-50 P Plug



TOUCH MODELS

(With Side-Opening Door & Humidity)

Same as Touch models above, except:

- Door auto-locks at start of cooking cycle
- Door opens automatically at end of cooking cycle. (Unit does not beep.)

				•		. ,	
Model	Description Cavity size: W" x H" x D"	Size/ Shelves	Volts	Watts	Amps	Unit Dimensions W" x H" x D"	Ship Wt. (lbs.)
XAFT-04HS-TR	19 1/4 x 13 1/4 x 14; 2.1 cft. One fan. NEMA 6-20P plug.	Half 4	208-240	2400-3300) 16	23 5/8 × 19 7/8 × 29	139*
XAFT-04FS-TR	27 $1/4 \times 13 1/4 \times 19$; 4 cft. Two fans. NEMA 6-50P plug.	Full 4	208-240	7600	32	31 1/2 x 19 7/8 x 35 1/2	190*

VENTLESS HOODS





The Cadco ventless hood is an ideal solution for installing your BAKERLUX™ TOUCH or LED oven anywhere in your kitchen, making it possible to cook when traditional Type-I hoods and duct-work are impractical or too expensive. This hood is a vapor capture and condensing system which removes odors and grease laden vapors expelled by the exhaust and when opening the oven door. No outside venting required. Certified ANSI UL 710B approved recirculating hood systems.

*Subject to verification and approval by authorities and local regulations

VENTLESS HOODS NSF UL CSA • UL 710B Emissions

- Compatible with LED and TOUCH oven models only
- Includes electro valve for direct plumbed water connection
- Freight class 200
- Ship wts:
 - *incl. skid, if ordered separately;
 - ** if factory installed on oven
 - *** Water hookup required
- All Hoods include factory installation unless ordered separately



Model	Description	Volts	Watts	Amps	Unit Dimensions W" x H" x D"	Ship Wt. (lbs.)
XAKHT-HCHS	Half Size. NEMA 6-	208-240 I SP plug.	200	I	23 5/8 x 10 7/8 x 28 25/32	89* 49**
XAKHT-HCFS	Full Size. NEMA 6-	208-240	200	I	31 1/2 x 10 7/8 x 34	92* 52**

Shown:

(1) XAKHT-HCFS Hood, (2) XAFT-4FS-TD ovens, (1) XWKQT-04EF-E Stacking Kit, (1) XAKPT-08FS-C Proofer

PROOFERS



PROOFERS for BAKERLUX™

LED & TOUCH Series Digital Ovens

NSF MET (UL & CSA)

- Handle 8 sheet pans (not included) ITemperatures to I22° F
- Adjustable legs or optional casters
- Freight class 200. **NOTE:** These models must ship by truck, not UPS *Ship weights include shipping skid (approx. 40 lbs.)
- NOTE: Oven & proofer are both controlled by the control panel on the oven
- Proofers are not designed for stand-alone use
- Proofers require water hookup





Model	Description	Size/	Volts	Watts	Amps	Unit Dimensions W" x H" x D"	Ship Wt. (lbs.)
XAKPT-08HS-C	Handles 8 half size sheet pans. NEMA 6-15P plug.	Half	208-240	1300	5.5	23 5/8 x 35 7/16 x 28	129*
XAKPT-08FS-C	Handles 8 full size sheet pans. NEMA 6-15P plug.	Full	208-240	1300	5.5	31 1/2 x 35 7/16 x 31 3/16	137*

BAKERLUX COOKING STATIONS

ONE MODEL NUMBER FOR SINGLE OR DOUBLE STACK CONVECTION OVENS



Full or half size convection ovens, with or without moisture capturing (ventless) hood systems.

All Bakerlux Cooking Stations come standard with stacking kit (*for double units*) and heavy duty stand.



Available in AutoQuotes



Industry Leading 3 Year Warranty



In Stock with Low Lead Times





Speed Oven

No more chewy sandwiches! VariKwik utilizes tri-heat technology, a balanced mix of conduction, convection, and infrared heat - with no microwave

Perfect for coffee shops, sandwich chains, bars, pubs, pizza shops, food trucks & much more!
Never compromise food taste & texture again and keep the money in your pocket - with VariKwik



No Microwave

Never compromise food taste & texture



Budget Friendly

1/3 of the price of competing speed ovens



Small Footprint

Made to fit any space & any application

VariKwik Speed Ovens





Larger Control Panel

VariKwik+ features a larger, 7" screen with updated graphics.



Small Footprint

With a compact design, VariKwik+ fits seamlessly into any kitchen.



No Microwave

VariKwik+ uses no microwave, ensuring evenly cooked-through food.



User Friendly

Updated interface is both intuitive and user-friendly.



Simplified Maintenance

The included CrisPlate is removeable and dishwasher-safe.



American-Made Durability

Heavy-duty stainless steel construction, made in the USA.





Model	Finish	Cooking Area	Volts	Watts	Amps	Unit Dimensions (W" x H" x D"	Ship Wt. (lbs.)
VK-120	Charcoal	14" x 10"	120	1650	16	24 x 12.5 x 23.75	77
VK-120-SS	Stainless	14" x 10"	120	1650	16	24 x 12.5 x 23.75	77
VKII-220	Charcoal	14" x 14"	220	4200	19.1	24 x 12.5 x 26.75	82
VKII-220-SS	Stainless	14" x 14"	220	4200	19.1	24 x 12.5 x 26.75	82
VKII-220-SS+	Stainless	14" x 14"	220	4200	19.1	24 x 12.5 x 26.75	82

FAST COOKING OVENS - Accessories









NEMA 6-20 P Plua

These hoods for the VariKwik™ ovens are an ideal solution for installing your oven anywhere in your facility, or where a traditional hood is unavailable. These hoods remove odors and grease laden vapors expelled by the exhaust. No outside venting required. (Subject to verification and approval by authorities and local regulations.)

Ventless Hoods for VariKwik™ Ovens

- Compatible with VariKwik™ oven models only
- Stainless with charcoal finish
- W: 22 19/32" x H: 10 3/4" x D: 30 11/32"
- Ship Wt.: 45 lbs. I Freight class 200
- Patent pending
- NOTE: Hoods do not fit on VKII-220-SS ovens
- VK-VHI: 120V, 70W, 1A, NEMA 5-15P plug
 VK-VH2: 220V, 70W, .5A, NEMA 6-20P plug

Hoods are approved to the following standards: UL197 & CSA C22.2 No. 109 and UL710B emissions

VARIKWIK™ OVENS - NSF & UL LISTINGS

NSF/ANSI Standard 4 (www.nsf.com) Listed as Cadco, Ltd.

UL Listed to requirements of UL 197 & CSA C22.2 No. 109

VariKwik™ Ovens: Listing ID E193933

For VariKwik Hoods listings, visit www.cadco-ltd.com

Refer to www.cadco-ltd.com for latest update on hood maintenance & filters information.

FAST COOKING OVENS - Accessories

VariKwik™ ovens have many accessories to meet your every need




VK-SK: Stacking Kit for VariKwik™ Ovens

- Everything needed to securely stack one VK series oven on top of another.
- Protects the top unit from heat rising from bottom unit.
- Oven spatula slot in front
- Stainless 90 day warranty Ship Wt.: 5 lbs.



CNB-VK: VariKwik™ Food / Nacho Basket

- Used in VariKwik ovens for foods that may not go directly on internal heat plate
- Flat bottom for maximum conductive heat transfer and perforated sides for consistent airflow
- Aluminum
- W: 13 1/8" × H: 11/8" × D: 10 1/2"
- 30 day initial defect warranty
- Ship Wt.: 2 lbs.



CrisPlates for VariKwik™ Ovens

- Specifically designed for VariKwik™ ovens (one comes standard in every oven)
- Aluminized steel with hard coat anodized non-stick baking surfaces
- Plates help ovens maintain better temperature stability
- 30 day initial defect warranty
- CrisPlate™ & design is a trademark of Cadco, Ltd.
- NSF & UL

CCP-VK: for VK-120/220 Ovens • W: 14" x H: 2 1/4" x D: 11 1/2" | Ship Wt: 5 lbs **CCP-VKII:** for VKII-220 Ovens • W: 14" x H: 2 1/4" x D: 15" • Ship Wt.: 6 lbs.



COS-I: Cadco Oven Spatula

- Large spatula to get food in and out of ovens easily
- One also included in every VariKwik™ oven
- Durable aluminum construction Insulated vinyl handle
- W: 12" x H: 1 1/8" x D: 18 1/2" 30 day initial defect warranty Ship Wt.: 2 lbs.



Cadco Heavy-Duty Manual Countertop Convection Ovens perform similarly to the Digital Convection Ovens, except with manual controls. Ideal for chains and individual foodservice operations.











- Advanced airflow design for even baking
- Heat settings from 175° 500° F
- 60 minute timer or continuous on
- Timer beeps at end of cycle
- Heavy duty stainless steel construction
- Extra large motor for long lasting use
- 3" between shelves
- Interior light
- "Cool-touch" double wall glass door
- Energy efficient
- Heavy duty door and hinge construction
- Requires dedicated electrical line
- All models stackable with Cadco Stacking Kit
- 2 Year Limited On-site Warranty

CONVECTION Ovens HEAVY DUTY MANUAL



XAF-133 shown

HALF SIZE MODELS (With Humidity)

- Shelves included
- Handles standard half size sheet pans (not included)
- Includes EL080 Auxiliary Water Pump
- Freight class 200.

NOTE: These models must ship by truck, not UPS

*Ship weights include shipping skid (approx. 40 lbs.







Model	Description	Shelves	Volts	Watts	Amps	Unit Dimensions	Ship Wt.
XAF-113	Cavity size:W" x H" x D" 19 1/2 x 10 x 15 1/2; 1.75 cft. One fan. NEMA 5-15P plug.	3	120	1450	12	W" x H" x D" 23 5/8 x 16 7/8 x 28 1/8	(lbs.) 120*
AF-133	19 1/2 × 13 × 15 1/2; 2.27 cft. One fan. NEMA 6-20P plug.	4	208-240	2700	20	23 5/8 × 20 × 28 1/8	125*



FULL SIZE MODELS (With Humidity)

- Shelves included
- Handles standard full size sheet pans (not included)
- Automatically reversible fan for even heat
- Includes electro valve for direct plumbed water connection
- Freight class 200.

NOTE: These models must ship by truck, not UPS *Ship weights include shipping skid (approx. 40 lbs.



Model	Description	Shelves	Volts	Watts	Amps	Unit Dimensions	Ship Wt.
XAF-183	Cavity size:W" × H" × D" 27 I/4 × I0 × I8 3/4; 3 cft. One fan. NEMA L6-30 plug	3	208-240	4600	20	W" x H" x D" 31 I/2 x 19 7/8 x 32	(lbs.) 180*
XAF-193	27 1/4 x 13 x 18 3/4; 3.85 cf Two fans. NEMA L6-30 plug		208-240	5900	24.6	31 I/2 × 23 × 32	190*



Cadco Medium-Duty Manual
Countertop Convection Ovens
perform similarly to the Digital
Convection Ovens, except with
manual controls. Ideal for chains
and individual foodservice
operations.







- Advanced airflow design for even baking
- Heat settings from 175° 500° F
- 60 minute timer or continuous on
- Timer beeps at end of cycle
- Heavy duty stainless steel construction
- Extra large motor for long lasting use
- 3" between shelves
- Interior light
- "Cool-touch" double wall glass door
- Energy efficient
- Heavy duty door and hinge construction
- Requires dedicated electrical line
- All models stackable with Cadco Stacking Kit
- 2 Year Limited On-site Warranty

CONVECTION Ovens MEDIUM DUTY MANUAL



OUARTER & HALF SIZE MODELS

(No Humidity)

- Shelves included
- Handles standard sheet pans (not included)
- Freight class 200. NOTE: Model OV-023 must ship by truck, not UPS *OV-023 ship weight includes shipping skid (approx. 40 lbs.) (OV-003 & OV-013 UPS-able if overwrapped. \$10/carton fee applies.)







0	/_ 0	13	ch	OV	vn
\mathbf{C}	/-U	ıs	211	IUV	VII

Mode	Description Cavity size: W"x H"x D"	Size	Shelves	Volts	Watts	Amps	Unit Dimensions W" x H" x D"	Ship Wt. (lbs.)
OV-003	14 1/8 x 9 x 11 1/4; .83 cft. NEMA 5-15P plug.	Quarter	3	120	1450	12	18 7/8 x 15 3/4 x 21 1/2	55
OV-013	, ,	Half	3	120	1450	12	23 5/8 x 15 3/4 x 23 3/4	68
OV-023	18 3/4 x 11 3/4 x 13 3/4; 1.75 cft. NEMA 6-15P plug.	Half	4	208-240	2700	11.25	23 5/8 x 18 5/8 x 23 3/4	120*

CONVECTION Ovens

SPECIALTY MANUAL



OV-013SS HALF SIZE CATERING CONVECTION OVEN

- Stainless steel door
- Light enough to carry to catering sites
- Handles half size standard sheet pans (not included)
- Freight class 200.
- UPS-able if overwrapped. \$10/carton fee applies.)





OV-023P HALF SIZE PIZZA CONVECTION OVEN

- 4 half size Pizza Heat Plates included (not wire rack shelves)
- Handles half size standard sheet pans (not included)
- Freight class 200

NOTE: Must ship by truck, not UPS

*OV-023P ship weight includes shipping skid (approx. 40 lbs.)



Model Description Cavity size: W"x H"x D"	Size	Shelves	Volts	Watts	Amps	Unit Dimensions W" x H" x D"	Ship Wt. (lbs.)
OV-013SS 18 3/4 x 9 x 13 3/4; 1.34 cft. NEMA 5-15P plug.	Half	3	120	1450	12	23 5/8 x 15 3/4 x 23 3/4	71
OV-023P 18 3/4 x 11 3/4 x 13 3/4; 1.75 cft. NEMA 6-15P plug.	Half	4 Heat Plates	208-240	2700	11.25	23 5/8 × 18 5/8 × 23 3/4	140*

ACCESSORIES

STACKING KITS

• Protects the top oven's control panel from heat rising from bottom oven • 90 day warranty



- Designed for BAKERLUX™ series ovens only
- Everything needed to securely stack one BAKERLUX™ oven on top of another

XWKQT-00HS-E: Stacking Kit for Half Size BAKERLUXTM Ovens

Ship Wt: 14 lbs.

XWKQT-04EF-E: Stacking Kit for Full Size BAKERLUXTM Ovens

· Ship Wt: 18 lbs.



- Designed for XAF series Manual ovens only.
- Everything needed to securely stack one XAF oven on top of another.

CXC651: Stacking Kit for Half Size XAF Manual Ovens

• Ship Wt: 5 lbs.

CXC646: Stacking Kit for Full Size XAF Manual Ovens

• Ship Wt: 8 lbs.

CONVECTION OVEN STANDS

For additional oven accessories, see pages 17 - 18





OST-195-CS Shown with Stacking Kit



OV-HDS: Heavy-Duty 2-Oven Stand w/ Wheels for Half or Quarter Size Ovens

- Stainless steel (assembly required)
- Silent casters (2 with brakes; 2 with directional locks)
- Unit: W: 25 3/4" x H: 42 3/8" x D: 30 1/4"
- Ship Wt: 56 lbs. (ships in 2 cartons)
- Freight class 200
- 90 day warranty

OST-195-C: Heavy-Duty Stand w/ Wheels for Full Size Ovens

- Handles 10 full size sheet pans (not included)
- Aluminum (ships assembled)
- Silent casters (2 with brakes; 2 with directional locks)
- Unit: W: 30" × H: 40" × D: 27"

- Ship Wt: 62 lbs.
- Freight class 200
- 90 day warranty
- NSF approved

OST-195-CS: Short Heavy-Duty Stand w/ Wheels for Full Size Ovens

- Handles 5 full size sheet pans (not included)
- Aluminum (ships assembled)
- Silent casters (2 with brakes; 2 with directional locks)
- Unit: W: 30" x H: 26 1/4" x D: 27"

- Ship Wt: 50 lbs.
- Freight class 200
- 90 day warranty
- NSF approved

OST-34A-C: Heavy-Duty Stand w/ Wheels for Half Size Ovens

- Handles 10 half size sheet pans (not included)
- Aluminum (ships assembled)
- Silent casters (2 with brakes; 2 with directional locks)
- Unit: W: 22" x H: 40"x D: 27"

- Ship Wt: 60 lbs
- Freight class 200
- 90 day warranty
- NSF approved

OST-34A-CS: Heavy-Duty Stand w/ Wheels for Half Size Ovens

- Handles 5 half size sheet pans (not included)
- Aluminum (ships assembled)
- Silent casters (2 with brakes; 2 with directional locks)
- Unit: W: 22" x H: 26 1/4" x D: 27

- Ship Wt: 48 lbs
- Freight class 200
- 90 day warranty
- NSF approved

ACCESSORIES

PIZZA HEAT PLATES



These exclusive Heat Plates bake everything in shorter time... for fast baking of Pizza, Breads, Snacks, and Baked Goods







- Up to 50% faster than traditional baking pans. It takes as little as 4-5 minutes to bake a fresh Pizza on a Heat Plate!
- Provides superior heat storage and produces fast, even cooking of both top and bottom of food product
- Plates help ovens maintain better temperature stability



- Aluminum

 Along surfaces

 20 day initial defeat warrants
- 30 day initial defect warranty

CrisPlate™	ic a	trademark	$\circ f$	Cadco	I+d
Cristiale	15 d	. li auemark	OI	Cauco,	Llu.

Model	Size	Unit Dimensions W" x H" x D"	Ship Wt. (lbs.)
CAP-Q	Quarter	13 1/2 x 1/4 x 91/2	4
CAP-H	Half	$183/8 \times 1/4 \times 12$	7
CAP-F	Full	26 1/4 × 1/4 × 17 7/8	13

OVEN BASKETS

Enhance even airflow around food for quicker, crisper results

APPLICATIONS: • Potato Puffs, Hash Browns, Roasted Potatoes • French Fries

- Chicken Wings Chicken Nuggets and Tenders Shrimp, Fish Sticks, Battered Fish
- Onion Rings | Roasted Vegetables Corn Dogs, Mozzarella Sticks, Stuffed Jalapeños, Etc.





- Stainless steel
- 30 day initial defect warranty

Model	Size	Unit Dimensions	Ship Wt.
		W" x H" x D"	(lbs.)
COB-Q	Quarter	127/8 x 11/4 x 9 1/2	2
СОВ-Н	Half	17 7/8 × 1 1/4 × 12 3/4	3
CORE	Eull	25 3/4 × 11/4 × 20	4

PANS & MORE



OQFSP: Quarter Size Flat Sheet Pan OHFSP: Half Size Flat Sheet Pan

- Fit an extra row of cookies vs. standard sheet pans
- Lower sides for easy removal of cookies, etc.
- Aluminum
 30 day initial defect warranty

OQFSP: I Unit: W: 13 1/2" x D: 10" x H: 7/16" • Ship Wt: 2 lb. **OHFSP:** I Unit: W: 18" x D: 12" x H: 7/16" • Ship Wt: 2 lb.



Cooling Rack for Sheet Pans

- Stainless steel
- Holds 3 standard sheet pansl 2" between pans/shelves
- 30 day initial defect warranty

OCR-Q3(Quarter Size): • Unit:W: 15.2 × D: 12.25 × H: 6.6" • Ship Wt: 10 lb. **OCR-H3** (Half Size): • Unit:W: 19 3/4" × D: 14 1/2" × H: 6.6" • Ship Wt: 11 lb.





XC606: Oven Air Deflector Plate


- Deflects air in oven cavity; for baking delicate foods like puff pastry
- Attaches without tools to the fan protection grid in the oven cavity
- Use one air deflector plate per oven fan
- \bullet Unit: Diam: 7 1/8" \times H: 3/4" \bullet Ship Wt: 1 lb.
- 30 day initial defect warranty

ACCESSORIES



ZW013SS: Stainless Steel Door

- Designed to fit OV-013 series Ovens
- Ideal for caterers
- Unit: W: 23 5/8" x D: 4 1/2" x H: 12 1/2"
- Ship Wt: 20 lbs.
- I year warranty on door/ 90 days on inner glass




OV013CB: Carry Bag

- Designed to fit OV-013 series Ovens
- Ideal for carrying ovens to catering jobs
- Bag sides open for easy placement of/ access to oven, & close with Velcro® closures.
- Black, heavy-duty vinyl material
- Sturdy carry straps wrap fully under bag for optimum bag strength
- 90 day warranty
- Unit Dimensions: W: 23 3/4" x D: 24" x H: 17 1/4" | Ship Wt: 4 lb.



XC615: Water Connection Kit

- Hose & connector to connect two stacked XAFT Digital Ovens with humidity, for sharing water hookup
- Ship Wt: I lb.
- 90 day warranty



GASKETS FOR OV SERIES OVENS:

GN1235AO: Gasket for OV-003 | Ship Wt: | lb. GN1230AO: Gasket for OV-013 | Ship Wt: | lb. GN1235AO: Gasket for OV-023 | Ship Wt: | lb

• 90 day warranty

CONVECTION OVENS, PROOFERS & HOODS MODEL NUMBER CROSS REFERENCE for NSF, UL & MET LISTINGS

All convection ovens, proofers & related hoods made to Cadco Ltd. specs by UNOX S.p.A., Italy

NSF/ANSI Standard 4 (www.nsf.com) Listed as UNOX

MET Listed to requirements of UL 197 & CSA C22.2 No. 109 (http://corp.metlabs.com/safety/listing.asp)
Heavy-Duty Manual Convection Ovens: UNOX S.p.A., Listing ID E112912
Heavy-Duty Digital (Bakerlux) Convection Ovens: UNOX S.p.A., Listing ID E112912
Medium-Duty Convection Ovens: UNOX S.r.I., Listing ID E112716

MET Listed to requirements of UL 197 & CSA C22.2 No. 109 (http://corp.metlabs.com/safety/listing.asp)

Proofers: UNOX S.p.A. Listing ID E112912

UL Listed to requirements of UL 197 & UL710B emissions & CSA C22.2 No. 109 Convection Oven Hoods: UNOX S.p.A. Listing ID MH60114

For Cadco - UNOX cross-reference model numbers, visit cadco-ltd.com/warranty-service

Panini Grills





CPG-15 (Panini; Ribbed top plate) Also available: CPG-15F (Clamshell; Flat top plate)

• Extra large high-tech glass-ceramic grilling surface

• Adjustable thermostat up to 740°F

• Easy to clean stainless steel housing

- Slide-out grease tray
- Power light
- Cool-touch handle
- Freight class 200











CPG-15FC

	,,,,,,,,,	(Clamshell; F	lat top pla	te)			
Model	Grill Area	Plate Type	Volts	Watts	Amps	Unit Dimensions (W" x H" x D")	Ship Wt. (lbs.)
CPG-15	15.75" x 11.75"	Ribbed Top, Flat Bottom	208/240	3100	14	19 x 7.5 x 18	38
CPG-15F	15.75" x 11.75"	Flat Top & Bottom	208/240	3100	14	19 x 7.5 x 18	38
CPG-15FC	15.75" x 11.75"	Flat Top & Bottom	120	1800	14	19 x 7.5 x 18	38
CPG-BBQ	15.75" x 11.75"	Ribbed Top & Bottom	120	1800	14	19 x 7.5 x 18	38

GRILLS



- Extra large high-tech glass-ceramic grilling surface(s)
- Adjustable thermostat up to 740°F Easy to clean stainless steel housing
- Slide-out grease tray Power light
- Cool-touch handle(s) 4 non-skid feet Freight class 200









Panini Grills are Made in Italy

AVAILABLE CONFIGURATIONS:Single & Double Panini Grills - Ribbed Top Plates & Smooth Bottom Plates



Model	Description	Туре	Volts	Watts	Amps	Unit Dimensions W" x H" x D"	Ship Wt. (lbs.)	LIST
SINGLE M	IODEL							
CPG-10	One 9 7/8'' grill area. Ribbed top plate. NEMA 5-15P plug.	Single	120	1500	12.5	13 x 7 x 18	25	
DOUBLE	MODEL							
CPG-20	Two 9 7/8" grill areas. Ribbed top plates. NEMA 6-20P plug.	Double	208/240	3200	14.5	24 I/3 x 7 x I8	45	



- High-tech glass-ceramic grilling surface(s)
- Adjustable thermostat(s) up to 740°F
- Easy to clean stainless steel housing
- Slide-out grease tray
- Power light
- Cool-touch handles
- 4 non-skid feet
- Freight class 200

Panini Grills are Made in Italy







CPG-10FC(220)

AVAILABLE CONFIGURATIONS:

Single & Double Clamshell Grills - Smooth Top & Bottom Plates
Black or Clear Plates





Model	Description	Туре	Volts	Watts	Amps	Unit Dimensions W" x H" x D"	Ship Wt. (lbs.)
SINGLE MO	DEL						
CPG-10F	One 9 7/8" grill area. Smooth top plate. Black plates. NEMA 5-15P plug.	Single	120	1500	12.5	13 x 7 x 18	25
CPG-10FC(120)	One 9 7/8'' grill area. Smooth top plate. Clear plates. NEMA 5-15P plug.	Single	120	1500	12.5	13 x 7 x 18	25
CPG-10FC(220)	One 9 7/8'' grill area. Smooth top plate. Clear plates. NEMA 6-20P plug.	Single	208/240	1750	7.9	13 x 7 x 18	25
DOUBLE M	ODEL						
CPG-20F	Two 9 7/8" grill areas. Smooth top plates. Black plates. NEMA 6-20P plug.	Double	208/240	3200	14.5	24 I/3 x 7 x I8	45
CPG-20FC	Two 9 7/8" grill areas. Smooth top plates. Clear plates. NEMA 6-20P plug.	Double	208/240	3200	14.5	24 I/3 x 7 x I8	45

TOASTERS









- Heavy duty ProHeat® mica heating elements with two year elements warranty
- I" × 5" slots fit standard size bagels
- Manual ejector with keep-warm feature
- Manual timer control
- Pull-out crumb tray for easy cleaning Freight class 200



Toasters Made in England





Model	Description	Туре	Volts	Watts	Amps	Unit Dimensions W" x H" x D"	Ship Wt. (lbs.)
4 - SLOT	MODELS - Selector switch for 2 or	4 slot o	peration				
CBF-4M	Buffet toaster / metallic grey end panels. 2 manual timers / ejectors for 2 or 4 slot operation NEMA 5-15P plug.	4 slot	120	1750	14.5	15 1/2×9×8	12
CTW-4M	Standard toaster / metallic grey end panels. NEMA 5-15P plug.	4 slot	120	1745	14.5	13 1/2 × 9 × 8	П
CTW-4M(220) Standard toaster / metallic grey end panels. NEMA 6-20P plug.	4 slot	220	2350	10.6	13 1/2 × 9 × 8	П
CTS-4(220)	Standard toaster / heavy aluminum end panels. NEMA 6-20P plug.	4 slot	220	2350	10.6	13 1/2 × 9 × 8	П
6 - SLOT	MODEL - Selector switch for 2, 4 or	r 6 slot (operatio	n			
CTW-6M(220) Standard toaster / metallic grey end panels. NEMA 6-20P plug.	6 slot	220	2480	11.3	17 × 9 × 8	12

GRIDDLES









SPECIAL FEATURES

Medium-Duty Countertop Griddles:





• Not intended to be used more than 4-5 hours per day









SPECIAL FEATURES

Light-Duty Countertop Griddles:

- Even heat up to 400° F
- Cool-touch stainless steel handles
- Base immersible: easy cleaning
- Removable cordset
- Not intended to be used more than 2 hours per day

Plug	Plug						1 /
Model	Description	Color	Volts	Watts	Amps	Unit Dimensions W" x H" x D"	Ship Wt. (lbs.)
LIGHT-DUT	TY MODEL						
PCG-I0C	21" x 12" cooking area. NEMA 5-15P plug.	Stainless	120	1500	12.5	29* x 5 /2 x 2 /2	14
MEDIUM-D	UTY MODELS						
CG-10	21" x 12" cooking area. NEMA 5-15P plug.	Stainless	120	1500	12.5	241/2 x 8 1/4 x 17 7/16	25
CG-20	$21" \times 12"$ cooking area. NEMA 6-20P plug.	Stainless	220	1500	6.8	24 1/2×8 1/4×17 7/16	25
CG-5FB	12" x 21" cooking area. NEMA 5-15P plug. Space Saver model.	Stainless	120	1500	12.5	15 7/8 ×8 1/4 ×26 15/32	. 25

HOT PLATES - TUBULAR









- Variable heat control(s)
- Heat signal light(s) glows only during heat cycle
- Easy-to-clean stainless housings
- On/Off power switch
- Freight class 200









Model	Description	Type	Volts	Watts	Amps	Unit Dimensions W" x H" x D"	Ship Wt. (lbs.)
SINGLE BUF	RNER MODELS						
CSR-IT	6'' diameter tubular element. NEMA 5-15P plug.	Single	120	1100	9.2	4 x 4 /8 x 2 /4	8
CSR-3T	8'' diameter tubular element. NEMA 5-15P plug.	Single	120	1500	12.5	4 x 4 /8 x 2 /4	8
CSR-3T(220)	8'' diameter tubular element. NEMA 6-20P plug.	Single	220	1500	6.9	4 x 4 /8 x 2 /4	8
DOUBLE BU	JRNER MODELS						
CDR-IT	6'' diameter tubular elements. NEMA 5-15P plug.	Double	120	1650 (= 2 x 825)	13.8	2 /4 x 4 /8 x 2 3/ 6	12
CDR-ITFB	6'' diameter tubular elements. NEMA 5-15P plug. Space Saver model.	Double	120	1650 (= 2 x 825)	13.8	13 1/2 x 4 1/8 x 22 3/4	14
CDR-2TFB	8" diameter tubular elements. NEMA 6-20P plug. Space Saver model.	Double	220	3000 (= 2 × 1500)	13.7	13 1/2 x 4 1/8 x 22 3/4	14

HOT PLATES - CAST IRON









- Solid cast iron elements deliver heat evenly to pot/pan
- Heat signal light(s) glows only during heat cycle
- Variable heat control(s)
- Easy to clean housings
- Freight class 200









Model	Description	Туре	Volts	Watts	Amps	Unit Dimensions W" x H" x D"	Ship Wt. (lbs.)	
SINGLE B	URNER MODELS							
KR-I	71/8" diameter cast iron element. Black enameled housing. NEMA 5-15P plug.	Single	120	1500	12.5		9	
KR-S2	71/8" diameter cast iron element. Stainless housing. NEMA 5-15P plug.	Single	120	1500	12.5	11 1/2 × 3 × 14	9	
DOUBLE	BURNER MODELS							
CDR-2C	71/2" diameter cast iron elements. Stainless housing. On/Off power switch. NEMA 5-20P plug.	Double	120	2000 (= 2 × 1000)	16.7	21 1/4 × 4 1/8 × 12 3/16	20	
CDR-2CFB	71/2" diameter cast iron elements. Stainless housing. On/Off power switch. NEMA 5-20P plug. Space Saver model.	Double (120 (= 2 × 100	2000	16.7	13 1/2 × 4 1/8 × 22 3/4	20	
BACK OF	THE HOUSE MODELS							
LKR-220	9" diameter cast iron element. Stainless housing. NEMA 6-20P plug.	Single	220	2000	9.1	15 × 4 1/4 × 14	18	
CDR-3K	9" diameter cast iron elements. Stainless housing. On/Off power switch. NEMA 6-20P plug. Space Saver model.	Double	220	4000	18.2	15 x 4 1/4 x 25 1/2	28	

ELECTRIC CHAFERS/BUFFET SERVERS





- Efficient heat transfer throughout entire warming surface
- Heavy duty: complete stainless steel construction
- Pans, pan holders & rolltop lids removable
- Capillary thermostat(s) (155° to 205° F)
- Variable heat control with safety signal lights
- Elegant charcoal finish Freight class 200

WTBS-5N-HD





Model	Description	Size	Volts	Watts	Amps	Unit Dimensions W" x H" x D"	Ship Wt. (lbs.)
ELECTRIC (CHAFER MODELS						
WTBS-2N-HD	2 half size, 2 1/2" deep steam pans. I rolltop lid. I pan holder.	Medium	120	300	2.5	24 x 12 x 14 3/8	32
WTBS-3N-HD	3 third size, 2 1/2" deep steam pans. 1 rolltop lid. 1 pan holder.	Medium	120	300	2.5	24 x 2 x 4 3/8	32
WTBS-4N-HD	4 half size, 2 1/2" deep steam pans. 2 rolltop lids. 2 pan holders.	Large	120	600	5	45 x 12 14 3/8	47
WTBS-5N-HD	2 half size + 3 third size, 2 1/2" deep steam pans. 2 rolltop lids. 2 pan holders.	Large	120	600	5	45 x 12 14 3/8	47

More models on pg. 30. For pans & lids, see Cadco-ltd.com. • Also offered in stainless steel, see at Cadco-Ltd.com

ELECTRIC CHAFERS/BUFFET SERVERS

STAINLESS STEEL MODELS



WTBS-5N-HD-SS







WTBS-4N-HD-SS

WTBS-3N-HD-SS

WTBS-2N-HD-SS

- Efficient heat transfer throughout entire warming surface
- Heavy duty: complete stainless steel construction
- Pans, pan holders & rolltop lids removable
- Capillary thermostat(s) (155° to 205° F)
- Variable heat control with safety signal lights
- Freight class 200





Model	Description	Size	Volts	Watts	Amps	Unit Dimensions W" x H" x D"	Ship Wt. (lbs.)
ELECTRIC C	HAFER MODELS						
WTBS-2N-HD-SS	2 half size, 2 1/2" deep steam pans. I rolltop lid. I pan holder:	Medium	120	300	2.5	24 × 12 × 14 3/8	32
WTBS-3N-HD-SS	3 third size, 2 1/2" deep steam pans. I rolltop lid. I pan holder:	Medium	120	300	2.5	24 × 12 × 14 3/8	32
WTBS-4N-HD-SS	4 half size, 2 1/2" deep steam pans. 2 rolltop lids. 2 pan holders.	Large	120	600	5	45 × 12 14 3/8	47
WTBS-5N-HD-SS	2 half size + 3 third size, 2 1/2" deep steam pans. 2 rolltop lids. 2 pan holders.	Large	120	600	5	45 × 12 14 3/8	47

More models on pg. 30. For pans & lids, see Cadco-ltd.com. • Also offered in stainless steel, see at Cadco-Ltd.com

WARMING SHELVES

Rolltop lid may be used directly on top of WT-10-HD & WT-40-HD warming shelves without pans



WT-5-HD-SS

- Efficient heat transfer throughout entire warming surface
- Freight class 200


- Heavy duty: complete stainless steel construction
- Capillary thermostat(s) (155° to 205° F)
- Variable heat control with safety signal lights



Model	Description	Size	Volts	Watts	Amps	Unit Dimensions W" x H" x D"	Ship Wt. (lbs.)
STAINLESS STEEL WARMING SHELF MODELS							
WT-5-HD-SS	151/2" x 11" stainless warming surface.	Small	120	300	2.5	20 1/4 × 2 3/4 × 14 3/8	13
WT-10-HD-SS	19" x 11" stainless warming surface.	Medium	120	300	2.5	24 × 2 3/4 × 14 3/8	14
WT-40-HD-SS	Two 19" x 11" stainless warming zones.	Large	120	600	5	45 × 2 3/4 × 14 3/8	22

BUFFET SERVER & WARMING SHELF ACCESSORIES







• 90 day warranty • Ship Wt.: 5 lbs. I Freight class 200

More accessories on pg. 31. For pans & lids, see Cadco-ltd.com. • Also offered in stainless steel, see at Cadco-Ltd.com

WARMING SHELVES

Rolltop lid may be used directly on top of WT-10-HD & WT-40-HD warming shelves without pans



- Efficient heat transfer throughout entire warming surface
- Heavy duty: complete stainless steel construction
- Elegant charcoal finish
- Capillary thermostat(s) (155° to 205° F)
- Variable heat control with safety signal lights
- Freight class 200
- PS-TBS-HD panholder(s) required if using steam pans & rolltop lid on WTRT-10 -HD, WT-10-HD, WTRT-40-HD, or WT-40-HD





Model	Description	Size	Volts	Watts	Amps	Unit Dimensions W" x H" x D"	Ship Wt. (lbs.)
WARMING	SHELF WITH ROLLTOP LID M						
WTRT-10-HD	19" x 11" stainless warming surface. I rolltop lid. Fits 1 full size steam pan.	Medium	120	300	2.5	24 × 9 3/4 × 14 3/8	23
WTRT-40-HD	Two 19" x 11" stainless warming zones. 2 rolltop lids. Fits 2 full size steam pans.	Large	120	600	5	45 × 9 3/4 × 14 3/8	31
WARMING	SHELF MODELS						
WT-5-HD	151/2" x 11" stainless warming surface. Fits 1 half size steam pan.	Small	120	300	2.5	20 1/4 × 2 3/4 × 14 3/8	13
WT-10-HD	19" x 11" stainless warming surface. Fits 1 full size steam pan.	Medium	120	300	2.5	24 × 2 3/4 × 14 3/8	14
WT-40-HD	Two 19" x 11" stainless warming zones. Fits 2 full size steam pans.	Large	120	600	5	45 × 2 3/4 × 14 3/8	22

BUFFET SERVER & WARMING SHELF ACCESSORIES

PS-TBS-HD: Steam Pan Holder



- Holds 3 third size, 2 half size, or one full size 2-1/2" deep steam pans for optimum heat retention
- Stainless steel with charcoal finish W: 20 3/4" x H: 2 1/2" x D: 15"
- 90 day warranty Ship Wt.: 5 lbs. I Freight class 200

More accessories on pg. 31. For pans & lids, see Cadco-ltd.com. • Also offered in stainless steel, see at Cadco-Ltd.com

ELECTRIC CHAFERS / BUFFET SERVERS

Keep prepared food warm until ready to serve!



- Pans & pan holders removable
- Variable heat control with safety signal lights
- Snap action thermostat(s) (155° to 205° F)
- Cool-touch handles
- Freight class 200





Model	Description	Size	Volts	Watts	Amps	Unit Dimensions W" x H" x D"	Ship Wt. (lbs.)
ROLLTOP I	LIDS MODELS						
WTBS-2RT	2 half size steam pans. I rolltop lid. I pan holder.	Medium	120	300	2.5	26 x 3 /4 x 5 /4	25
WTBS-3RT	3 third size steam pans. I rolltop lid. I pan holder.	Medium	120	300	2.5	26 x 3 /4 x 5 /4	25
WTBS-4RT	4 half size steam pans 2 rolltop lids. 2 pan holders.	Large	120	600	5	46 x 3 /4 x 5 /4	40
WTBS-5RT	2 half size + 3 third size steam pans. 2 rolltop lids. 2 pan holders.	Large	120	600	5	46 x 3 /4 x 5 /4	40
INDIVIDUA	AL CLEAR LIDS MODELS						
WTBS-12P	I half size steam pan. I individual lids. I pan holder:	Small	120	300	2.5	18 1/4 × 7 7/8 × 15 1/4	14
WTBS-23P	2 third size steam pans. 2 individual lids. I pan holder.	Small	120	300	2.5	18 1/4 × 7 7/8 × 15 1/4	14
MULTI-LEV	'EL MODEL						
CMLB-24RT	4 half size steam pans. 2 rolltop lids. 2 pan holders.	Multi-Level	120	600	5	23 1/4 × 26 × 15 1/4	46

BUFFET SERVER & WARMING SHELF ACCESSORIES



PS-TBS: Steam Pan Holder

- Holds 3 third size, 2 half size, or one full size 2-1/2" deep steam pans for optimum heat retention
- Stainless steel W: 20 3/4" x H: 2 1/2" x D: 14 1/4"
- 90 day warranty Ship Wt.: 3 lbs. Freight class 200

For pans & lids, see Cadco-ltd.com.

WARMING SHELVES

- Variable heat control(s) with safety signal light(s)
- Easy-to-clean warming surface
- Snap action thermostat(s) (155° to 205° F)
- Freight class 200









Model	Description	Size	Volts	Watts	Amps	Unit Dimensions W" x H" x D"	Ship Wt. (lbs.)
SINGLE L	EVEL MODELS						
WT-5S	13 7/8" × 14" stainless warming surface. Fits I half size steam pan.	Small	120	300	2.5	18 3/4 × 3 × 15 1/4	9
WT-10S	201/2" × 14" stainless warming surface. Fits full size steam pan.	Medium	120	300	2.5	26 × 2 7/8 × 15 1/4	10
WT-40S	41 1/4" x 14" stainless warming surface. Fits 2 full size steam pans.	Large	120	600	5	46 × 2 7/8 × 15 1/4	21

WARMING CABINETS/BUFFET SERVERS











- Large 28" x 14" stainless warming surface on top level
- Lower cabinet may be used as a food / plate warmer
- 2-1/2" deep stainless steam pans Pans & pan holders removable
- 2 variable heat controls (one for top level, one for bottom) with safety signal lights
- Snap action thermostats (155° to 205° F) Freight class 200

Model	Description	Volts	Watts	Amps	Unit Dimensions W" x H" x D"	Ship Wt. (lbs.)
SINGLE LI	EVEL MODELS					
CMLB-CSG	2 half size & I third size steam pans. No lids. I pan holder:	120	600	5	28 × 22 1/2 × 18 1/4	48
NON-SNE	EZE GUARD MODELS					
CMLB-CSLP	2 half size & 1 third size steam pans. 3 poly lids with utensil slots. I pan holder.	120	600	5	28 × 14 × 15 1/4	42
MULTI-LE	VEL MODEL					
CMLW-2	Two 20 1/2" × 14" stainless warming surfaces Fits 1 full size steam pan per level	120	600	5	23 /4" x 6 /4" x 5 /4	32



Pass & Go WARMER

Keep food products warm & ready to serve with Cadco's latest product - the "Pass & Go Warmer"

Designed with ease of use and space efficiency in mind, serving products now became easier!



Plug & Play

Available in both 120v & 220v options



3 Sizes

Ranging from 27" wide to 52" wide



Easy To Use

Complete control of infrared & conduction





PGW-5 (28" Wide)



PGW-10 (40" Wide)




PGW-15 (52" Wide)

FEATURES

- Infrared heating element
- Stainless steel construction
- Pass-through design
- Made in the U.S.A.
- Individual top & bottom heating controls
- 120v plug & play design
- Stackable for maximum output*



Top Infrared Element



BUFFET SERVER & WARMING SHELF ACCESSORIES

Pans & Lids

• 30 day initial defect warranty • Freight Class 200



CL-3: Third Size Clear Lids Accessory Pack

- Three clear polycarbonate lids for third size steam pans
- Each lid W: 12 7/8" x H: *2 1/2" x D: 7 "
- Ship Wt.: 3 lbs. UL Sanitary

CL-2: Half Size Clear Lids Accessory Pack

- Three clear polycarbonate lids for third size steam pans
- Each lid W: 12 7/8" x H: *2 1/2" x D: 7 "
- Ship Wt.: 3 lbs. UL Sanitary



C-DPF2-HD

C-DPF2-HD: Clear Rolltop Lid

- Fits full size steam pan
- Eastman TritanTM copolyester material
- Corrosion-resistant metal hinges
- W: 21 1/2" x H: 7" x D: 13 1/4"
- Ship Wt.: 9 lbs. NSF



SPL-2P

SPL-3P: Third Size Steam Pan with Clear Lid

- One third size (2-1/2" deep) stainless steam pan w/clear lid
- W:12 7/8" × H:5" × D:7"
- Ship Wt.: 2 lbs. NSF

SPL-2P: Half Size Steam Pan with Clear Lid

- One half size (2-1/2" deep) stainless steam pan w/clear lid
- W:12 7/8" × H:5" × D:10 1/2"
- Ship Wt.: 2 lbs. NSF

BUFFET SERVER & WARMING SHELF ACCESSORIES

False Bottoms for Steam Pans



- Holds food above pan bottom for draining and/or keeping food moist
- Universal fit for corresponding steam table pan size (CDT-6 does not fit Carlisle pans)
- 1/2" height above pan bottom (3/8" on CDT-6)

- Small holes are 3/8" diameter
- Stainless steel
- Non-rusting
- Made in America
 NSF









CDT-6 shown in sixth size steam pan

CDT-6

- Sixth-size false bottom for steam pan
- Unit Dims: 5"W x 5 1/2" D x 3/8" H
- Unit Weight: 0.25 lb.
- Ship Weight: I lb.





CDT-3 shown in third size steam pan

CDT-3

- Third-size false bottom for steam pan
- Unit Dims: 5 9/32"W x 11 5/32"D x 1/2"H
- Unit Weight: 0.6 lb.
- Ship Weight: I lb.





CDT-2 shown in half size steam pan

CDT-2: Half-size False Bottom for Steam Pan

- Unit Dims: 9 5/32"W x 11 7/32" D x 1/2" H
- Unit Weight: 0.9 lb.
- Ship Weight: I lb.

WARRANTY & SERVICE INFORMATION

Unless otherwise noted, Cadco, Ltd. warrants all products (in the U.S only) to be free from defects in material and workmanship for a period of one year from date of purchase. (See product descriptions and warranty table for other warranty periods on specific models / parts) Warranty does not apply in cases of misuse, abuse, or damage from external service or repair attempts by unauthorized personnel.

NOTE: Using a Cadco oven without a gasket or with one in disrepair may cause the hinges to seize, as well as limit the oven's ability to maintain the proper temperature. Doing so will void the warranty on the hinges. Please inspect and clean the door gaskets daily.

Cadco national service number 877-603-7393 MUST be called first for authorization of any Warranty Service at any service location. Service centers available throughout the U.S. can be found by visiting www.cadco-ltd.com

Cadco is an Associate Member, Commercial Food Equipment Service Association

Copy of original invoice is required for proof of purchase date for warranty coverage (no registration required).

If returning a unit directly to Cadco, Ltd. for warranty repair, please call us first for a Return Authorization Number, which MUST be written on the outside of the carton to track the unit and avoid service delays.

The customer is responsible to ship or deliver carry-in service items to a Cadco authorized service center, or directly to Cadco. If shipping the unit, be sure to pack it securely and insure it for its original purchase price. Cadco is not responsible for damage or loss of unit in transit to us or a service center.

All carts: warranty applicable only in 48 contiguous U.S. states.

Please do not return units to the store where purchased for warranty repair.

Product Model or	On-Site Service	Carry-In Service		l year parts	excluding	30 days glass 90 days light bulbs & gaskets I year motor & fan	30 days laminate
Product Category		Service					lammate
VK-120 / VK-220 / VKII-220	X			X	X	X	
XAFT-03HS-GD / XAFT-03HS-EGDN-U				X	X	X	
XAFT-03HS-LD / XAFT-03HS-ELDV-US	X			X	X	X	
XAFT-03HS-TD / XAFT-03HS-ETDV-US				X	X	X	
XAFT-04HS-LD / XAFT-04HS-ELDV-US	X			X	X	X	
XAFT-04HS-TD / XAFT-04HS-ETDV-US				X	X	X	
XAFT-04HS-TR / XAFT-04HS-ETRV-US	X			X	X	X	
XAFT-04FS-LD / XAFT-04FS-ELDV-US	X			X	X	X	
XAFT-04FS-TD / XAFT-04FS-ETDV-US	X			X	X	X	
XAFT-04FS-TR / XAFT-04FS-ETRV-US	Х			X	X	X	
XAF-II3 / XAFTII3	X			X	X	X	
XAF-133 / XAFT133	X			X	X	X	
XAF-183 / XAFT183	X			X	X	X	
XAF-193 / XAFT193	X			X	X	X	
OV-003 / XAF003		X		X	X	X	
OV-013 / XAF013		X		X	X	X	
OV-023 / XAF023	X			X	Χ	X	
OV-013SS / XAF013		X		X	X	X	
OV-023P / XAF023	X			Χ	X	X	
Oven Hoods	X			X		X	
Proofers	Χ			X		X	
VK Warmers	X			X	X		
Panini & Clamshell Grills			Χ	X			
Griddles			Χ	X			
Hot Plates			X	X			
Toasters			Χ	X			
Warming Cabinets			X	X			
Electric Chafers / Buffet Servers			Χ	X			
Warming Shelves			Χ	X			
Mobile Food Carts	X			X			X
Mobile Beverage Carts	Χ			X			Χ
Mobile Demo Carts	X			X			X
Mobile Grab & Go Carts	X			X			X
Mobile Storage Carts	X			X			X

ORDERING & SHIPPING INFORMATION

The following models have a carton overwrap charge of \$10 per unit for all UPS/FEDEX shipments, including third-party billed shipments:

- OV-003, OV-013 & OV-013SS Convection Ovens
- There is a handling charge of \$5 per drop ship order.
- All carts Freight Class 250 and FOB 06098.
- Dimensions listed on all product pages are for assembled piece of equipment without shipping carton.



• Shipping weights listed on all product pages are for equipment packed in shipping carton, and include skid(s) where applicable.



- Due to continual product improvement, product specifications, designs and pricing are subject to change without notice.
- Products with the FastShip designation will ship within 2-3 business days of receipt of order within our system.

TECHNICAL & CHEF SUPPORT

We have the personnel for phone support to insure proper installation and answer aftermarket & food-related questions.

WEBSITE RESOURCES


VISIT OUR WEBSITE FOR USEFUL RESOURCES:

cadco-ltd.com






Cadco is represented throughout the United States and Canada by a select group of sales representatives. Experienced and knowledgeable sales reps provide valuable information and reliable support, from start to finish.



Scan the QR Code to view a current listing of Cadco Sales Reps





860-738-2500 • Fax: 860-738-9772

info@cadco-ltd.com • cadco-ltd.com